



A4 Thermal Receipt Printer

ITEM	ITEM DETAILS	PARAMETER
Printing	Print way	Thermal line printing
	Effective width	210mm/216mm Ådefault 216mm Å
	Print command	ESC
	Print speed	Max speed 45mm/s
	Print density	8 dots/mm Å203dpi) ,1728 dot/line
	Character size	12*24 Æ24*24
	Connection method	Android & iOS & Windows
	Interface	USB
	Bluetooth Printer	4.0 / Å4.0 or more Å
	Software function	Edit notes, photo search, text recognition, print templates, web page printing, Word printing PDF printing, Excel printing, picture printing
Paper	Paper width	216 f 1mm
	Support paper	Thermal paper
	Paper silo diameter	Can use the maximum outer diameter ¶ 30mm (installed in the machine) or ¶ 50mm (installed in the external paper bin) thermal paper roll.
	Paper thickness	0.05-0.15mm
	Paper loading method	Easy paper structure
	Paper Targeting	Photoelectric sensor
Reliability	Status Display	Out of paper, open cover, charge (LED indicator)
	Standby time	3days
	Print head life	50KM
	Full charge printing	50m
	Charging time	4 Hours
	Out of paper detection	Optocoupler detection
	lithium battery	1200mAh
	USB type	USB Micro USB interface
Adapter		DC 12V / 3A
Certificate		Appearance patent/CCC
Size	Machine size	265*93*53*mm
	Gift box	296 mmX210mmX78mm
Weight		1350g
Working environment		Tempt Ö0-45 Humidity Ö20-90%
Store environment		Tempt Ö-10-60 humidity Ö10-90% ÅExcept paper roll Å